


# SafEye

OPEN PATH GAS MONITORING SYSTEMS

# MODEL 200



**WELL-PROVEN HIGH RELIABILITY**



## MAIN FEATURES

### PROVEN TECHNOLOGY

Used in highly sensitive areas to detect low gas concentration levels to activate alarms measures only when specific hazardous concentration levels are exceeded.

Thousands installed on offshore platforms, FPSO's, refineries, etc., for British Petroleum (BP), Shell, ExxonMobil, Statoil and others.

### COST SAVING

One system can replace from 5 to 20 point gas detectors in a straight line of sight, up to 460 ft. (140 m). Low cost of ownership, much lower installation cost!

### FAST RESPONSE

Adjustable light source flash rate gives high sensitivity and extremely fast detection time. Also prevents detector going into obscuration when a large cloud of gas passes through the beam.

### HARSH ENVIRONMENT

Specially designed to perform under extreme conditions such as high-speed airflows, humidity and corrosive gases where point detectors may not be effective.

### LOW MAINTENANCE

High reliability, simple installation, alignment and maintenance, equipment not subject to poisoning.

### STANDARD INTERFACE OPTIONS

Standard 4-20 mA outputs or RS-485 output to allow networking (up to 64 detectors) to a central monitoring/PC system.

This feature also enables easy maintenance, local and remote diagnostic tools.



SafEye 200 Series Open Path Gas Detector is a self-contained, fast response optical gas detection system. It detects combustible gases at concentrations lower than the explosion limit (LEL) over a "Line of Sight" of up to 460 ft. (140 m) long.

SafEye is the preferred system for offshore oil companies because it is immune to false alarms caused by partial blockage and extreme weather conditions (fog, rain, snow) and direct or reflected sunlight, flame and other black body radiation sources.



The SafEye system can be factory calibrated to a gas mixture most probable to leak in a specific location. This results in the most accurate gas concentration measurement.

The SafEye is fully functional in heavy fog, rain, etc, that results in up to 90% of the signal obscuration. In a North Sea offshore installation, tested for over six harsh winter months which included very dense fog, snow and rain, the SafEye was fully operational at all times.

SafEye is built for reliability and continued operation under all types of extreme environmental conditions. This is the field experience, which is demonstrated by the SafEye operational installations, ranging from the very humid and hot Far East to the wet and cold North Sea to the dry and cold slopes of Alaska.

The SafEye, due to its special optics design, provides for a misalignment tolerance of  $\pm 1^\circ$  in all directions and is protected against false gas reading and alarms.

The SafEye unique flash source gives a very powerful radiation signal for a very short time, less than one millisecond at pre-selected intervals. This patented feature enables the detector to address only the high intensity and ultra fast signals that correspond to fast changes in gas concentration, while ignoring all other background radiation.

## GENERAL SPECIFICATIONS

<b>Detection Range and Response Time</b>	Model No.	202/252	203/253	204/254	226/256	227/257
	Distance (ft)	9.8-39	33-131	50-198	98-295	164-460
	Distance (m)	3-12	10-40	15-60	30-90	50-140
	Response Time	2 sec.	5 sec.	5 sec.	5 sec.	5 sec.
<b>Detected Gases</b>	C <sub>1</sub> -C <sub>8</sub> flammables by models 202-227, Ethylene / LPG by models 252-257.					
<b>Immunity to False Alarm</b>	Is not influenced by solar radiation, hydrocarbon flames and other external IR radiation sources.					
<b>Spectral Response</b>	3.0-4.0 $\mu$ m					
<b>Sensitivity Range</b>	0-5 LEL.m Standard 0-2 LEL.m by dip-switch setting					
<b>Displacement/Misalignment Tolerance</b>	$\pm 1^\circ$					
<b>Drift</b>	Long-term $\pm 5\%$ of full scale					
<b>Temperature Range</b>	-40°F (-40°C) to 131°F (55°C)					

## ELECTRICAL SPECIFICATIONS

<b>Power Supply</b>	Standard - 24 VDC (18-32 VDC)
<b>Power Consumption</b>	Detector: 150mA @ 24 VDC (200 mA Peak) Source: 100mA @ 24 VDC (220 mA Peak)
<b>Electrical Connection</b>	2 x 3/4" - 14NPT conduits or 2 x M25 x 1.5 mm ISO
<b>Electrical Input Protection</b>	Complete electrical interface protection against reversed polarity voltage, surges and spikes according to MIL-STD-1275A
<b>Electromagnetic Compatibility</b>	EMI/RFI protected CE Marked

## OUTPUTS

<b>4-20mA</b>	The 4-20mA current output is source configuration Resistance Loop 100-600 $\Omega$			
<b>RS-485</b>	Serial communication for full control with maintenance and trouble shooting facility can be integrated for a network of max 64 detectors			
<b>Relays</b>	Type	Normal Position	Maximum Ratings	
	Alarm	SPDT	NO, NC	2A at 30VDC or 0.5 at 250 VAC
	Accessory	SPST	Open	5A at 30VDC or 250VAC
	Fault	SPST	Closed	5A at 30VDC or 250 VAC

## MECHANICAL SPECIFICATIONS


<b>Dimensions</b>	5.2" (132mm) x 5.2" (132mm) x max. 11" (280mm)			
<b>Weight</b>	Al. Encl.	Detector: max 8.8 lb (4 kg)	Source: max 10.8 lb (4.9 kg)	
	St. Encl.	Detector: max 14.3 lb (6.5 kg)	Source: max 16.7 lb (7.6 kg)	
<b>Mechanical Design</b>	The standard detector housing is heavy-duty, copper-free (less than 1%) aluminum. The housing is finished in white epoxy enamel and is also available in 316L Stainless Steel* upon request. <i>* Carries an additional charge.</i>			
<b>Environmental Standards</b>	Meets MIL-STD-810C for Humidity, Salt & Fog, Vibration, Mechanical shock, High Temp, Low Temp			
<b>Water and Dust Tight</b>	IP66 and 67 NEMA 250 6P			

## HAZARDOUS AREA APPROVALS

<b>ATEX / Cenelec</b>	EX II 2G EExd IIB + H <sub>2</sub> T6 (55°C) EX II 2G EExde IIB + H <sub>2</sub> T6 (55°C)
<b>UL</b>	UL No. - E209870, Class I Groups C and D Hazardous Location
<b>GOST R</b>	Approved

## ACCESSORIES

The following optional accessories designed for the SafEye system are available.



### MOUNTING

- **Swivel mount** -The swivel mount is made of stainless steel 316L. The swivel mount enables the detector to rotate up to 30° in all directions and fine alignment of up to 3'. (P/N 794765).

- **Tilt device** - Stainless steel 316L, designed for easy and precise alignment. Enables the detector to rotate up to 30° in all directions and fine alignment of up to 5'. (P/N 796640)

### FUNCTION CHECK FILTER

Used for on-site functional testing of the detector (P/N 794260).

### ALIGNMENT TELESCOPE

Is used for simple on-site alignment of the detector with the light source. (P/N 794110)

### MAGNETIC SWITCH

The magnetic mode selector is used in the field to change the detector's modes for alignment and calibration procedures (P/N 790285).



## TYPICAL APPLICATIONS

Offshore Oil & Gas Exploration Oilrigs and FPSOs; Onshore Oil & Gas Terminals; Storage Farms and Filling Stations; Petrochemical and Chemical Industries; Power Utilities and Turbines areas; Waste Processing and Treatment; Transportation Terminals; Automotive, Painting, Printing, Pharmaceutical Industries and many more...

Specific applications include: • Fence-line emission monitoring • Process and storage areas • Control rooms and auxiliary equipment enclosures • Vessels and tanks roof monitoring • Bus garages and terminals (switching from diesel to natural gas) • Pipelines • LNG-LPG storage, pumping and filling • Paint-booths and paint production

## CONTACT INFORMATION

### NEW JERSEY

218 Little Falls Road, Cedar Grove, NJ 07009, USA  
Tel: +1 (973) 239-8398, 1 (800) 452-2107 (*Toll free US only*), Fax: +1 (973) 239-7614  
e-mail: [spectrex@spectrex-inc.com](mailto:spectrex@spectrex-inc.com)

### UK

6 Applecross Road, Glasgow G66 3TJ, United Kingdom  
Tel: +44 (0) 141 578 0693, Fax: +44 (0) 141 578 9689  
e-mail: [ian@spectrex-inc.com](mailto:ian@spectrex-inc.com)

### HOUSTON

4723 Hidden Springs, Houston, TX 77084, USA  
Tel: +1 (281) 463-6772, Fax: +1 (281) 463-1134  
e-mail: [jay@spectrex-inc.com](mailto:jay@spectrex-inc.com)

Represented by:

